POLESTAR
نجم القطب
Polestar Worldwide General Trading LLC

Base oil SN150 (Recycled)

Recycled base oils are primarily used in lubricant production and as blending components for other grades. They undergo a refining and de-waxing process. To finish refining, they are treated with hydrogen to clear impurities. They are acclaimed for their good solubility, color stability, low volatility, pleasant odor, fair viscosity index, low sulfur content, and low ash content.

Advantages

1) Highly saturated, Low volatility, Low aromatics or impurities
2) Improved demulsibility, Light color
3) Good solubility characteristics
4) Uniform composition, good oxidation, Color stability, High viscosity Index

Parameter	Unit	Test Method	Value
Color ASTM	-	D1500	1.5-2.0
Density @ 15°C	(kg/L)	D1298	865-875
Kinematic Viscosity @ 40 °C	cSt	D445	50-60
Kinematic Viscosity @ 100°C	cSt	D445	7.56
Flash Point (COC)	°C	D92	193
Pour Point	°C	D97	-2
Viscosity Index	Typical	D2270	110
Appearance	-	Visual	Clear and Bright

Uses

1)Industrial burners, engine oils
2)Rubber process oils and metalworking oils
3)Mold oil to help release products from their molds
4)For mixing in Bitumen base products
5) Additives in manufactured products, such as lubricants, transformer oils, and high-speed spindle machines.

Comments: The specifications as mentioned above may vary depending on the origin and batch. For updated specifications related to your order, please don't hesitate to contact a sales representative at Polestar Worldwide General Trading LLC.

+971 04 513 5655
+971 04 513 5656
www.polestarworldwide.ae
P O Box Number : 13866
export@polestarworldwide.ae
inquiry@polestarworldwide.ae